

IP Video Surveillance

VB7255 Bullet Camera

1.3MP HD 720p



Overview

VIDEOTEKNIKA VB7255 is a versatile, fully cable managed, varifocal bullet camera designed for outdoor applications with a 1.3 Megapixel sensor enabling a viewing resolution of 1280 x 960 (720p HD Real Time). The outdoor True Day & Night camera provides superior quality video in the most extreme low light conditions upto 50 metres with an additional feature of IR-cut filter with auto-switch (ICR). The VB7255 features a 3-Axis adjustment bracket. The camera incorporates a 1/3" CMOS chip with progressive scan technology enabling sharp images in highly populated locations. The VB7255 also supports POE.

Supported Compression

The VB7255 supports MJPEG compression technology, a digital video encoding standard where each video frame is separately compressed into a JPEG image. The VB7255 also supports the industry standard H.264 compression, the most recent compression technology that reduces drastically video file sizes therefore allowing for better storage and lowers bandwidth demands.

Dual Streaming

The VB7255 allows for dual independent streaming images to pass through the video coder. The resolution, frame rate and bit rate can be set independently on both streams. The main application for dual streams allows for high resolution and high frame rate streaming for recording while allowing lower resolution and frame rate for computer browsing and mobile device applications.

Supported Software

The Camera is supported by the Videoteknika VVMS-*Xpert*™ VMS. The VVMS-*Xpert*™ VMS is a modular Video Management Software dedicated for Videoteknika IP cameras expandable up to 1024 Channels per server. A 64 Ch version VVMS-*Advanced*™ is supplied as a free bundled software with all Videoteknika IP Cameras. VVMS-*Mobile*™ is also available on Iphone and Android applications. Videoteknika IP cameras are supported by various leading software development VMS partners.

Main Features

- HD (720p) Real time video
- Up to 1.3 Megapixel (1280 x 960) Resolution
- 1/3" progressive scan CMOS
- Built-in IR Illuminator, Effective 50 metres
- True Day & Night IR Cut filter with auto-switch
- Digital Wide Dynamic Range
- Varifocal Lens 2.8 ~ 12mm
- Dual Simultaneous Streaming
- Supported Video Compressions : MJPEG / H.264
- Fully cable managed Housing and Bracket (IP66 rated)
- Power Over Ethernet (POE)
- NAS – Network Storage Compatible
- ONVIF,PSIA,CGI compatible
- Videoteknika – VVMS-*Advanced*™ VMS software included
- Videoteknika – VVMS-*Mobile*™ supported on App Store
- Built-in Micro SD / SDHC card slot for local storage

VB7255

IP 1.3MP Bullet

HD 720p



IP Video Surveillance

VB7255 Bullet Camera

1.3MP HD 720p



Easy setup

- Fully cable managed Housing and Bracket (IP66 rated)
- Power Over Ethernet – POE (802.3af)
- Varifocal Lens 2.8 ~ 12mm
- True Day & Night IR Cut filter with auto-switch
- Built-in IR Illuminator, Effective 50 metres
- Saturation, brightness, contrast adjustable through client software or web browser


Typical Camera Locations	VB7255
Retail	Yes
Banking	Yes
Airports	Yes
Hotels & Hospitals	Yes
Parking garages	Yes
Traffic Surveillance	Yes
Perimeter Protection	Yes
Stadiums	Yes
Playgrounds	Yes

Specifications

Camera Model	VB7255
Features	
Image Sensor	1/3" Progressive Scan CMOS
Min. Illumination	0 Lux with IR
IR Range	50 metres
Shutter time	1/25s (1/30s)~1/100,000s
Lens	2.8 ~ 12 mm @F1.4 Angle of view: 98° ~ 30.2°
Lens Mount	φ14
D-WDR	Digital Wide Dynamic Range
Local Storage	Built-in Micro SD slot, up to 32 GB
Communication	1 RJ45 Ethernet port
Day and Night	IR cut filter with auto switch
System Compatibility	ONVIF, PSIA, CGI
Video Compression	H.264/ MJPEG
Bit Rate	32 Kbps ~ 16 Mbps
Dual Stream	Yes
Max. Image Resolution	1280 x 960
Frame Rate	50 Hz: 25 fps (1280 x 960), 25 fps (1280 x 720) 60 Hz: 30 fps (1280 x 960), 30 fps (1280 x 720)

Camera Model	VB7255
Features (Continued)	
Image Settings	Saturation, brightness, contrast adjustable through client software or web browser
Network Storage	NAS – Network Storage Compatible
Alarm Trigger	Motion detection, network disconnect, IP address conflict, storage exception
Security	Password protection, watermark
Environmental	
Operating Temperature	-30 °C ~ 60 °C (-22 °F ~ 140 °F)
Electrical	
Input Voltage	12 VDC ± 10%, PoE (802.3af)
Power Consumption	Max. 5.5W (7.5W with ICR on)
Physical	
Dimensions	95(W) x 105(H) x 258.6(D) mm
Weather Proof	IP66
Weight	1200 g (2.64 lbs)
Regulatory Certifications	FCC, CE, C-TICK, UL

Dimensional Diagrams



IP Video Surveillance
 VB7255 Bullet Camera
1.3MP HD 720p



Ordering Information

Camera Model	Camera Details
VB7255	1.3MP (1280 x 960) HD 720p, True Day & Night, Varifocal 2.8 ~ 12mm, Dual Streaming, IP66 rated, PoE, D-WDR, Fully cable managed 3-Axis Bracket, VMS Support, Mobile Support, NAS Network Storage Support, SD Card.
VB7555	3MP (2048 x 1536) Full HD 1080p, True Day & Night, Varifocal 2.8 ~ 12mm, Dual Streaming, IP66 rated, PoE, D-WDR, Fully cable managed 3-Axis Bracket, VMS Support, Mobile Support, NAS Network Storage Support, SD Card.

Recommended Associated Products



BRACKETS	VBB-01	VBB-02	VVMS -Advanced™
Mount :	Pole Mount Bracket	Power Intake Box	Video Management Software
Dimension :	117 (W) x 194 (L) x 143 (H) mm	90 (W) x 90 (L) mm	64 Channel Mobile Application

Affiliations:



Partners:

